


# MJ 邁鈞機械工業股份有限公司

LP-770PBS200調整式球心型高速研磨機(光學鏡片加工用)  
ADJUSTING & SPHERICAL CENTER OF HIGH SPEED  
GRINDING MACHINE (OPTICAL LENS PROCESSING)



各軸單動  
Individual axle  
control

邁鈞機械工業股份有限公司  
MAI JIUN MACHINERY CO., LTD  
412-80 台灣台中市大里區仁化里工業十路8號  
NO. 8, GONGYE 10TH RD., RENHUA LI,  
DALI DIST., TAICHUNG CITY, 412-80 TAIWAN  
TEL: 886-4-24912698 FAX: 886-4-24915811  
E-mail: mai.j.mail@msa.hinet.net

770加大型  
770Extra Large

770(加大型)調整式球心型高速研磨機(光學鏡片加工用)-機台規格表 SPECIFICATION

A05

機型	Type	LP-770PBS200S	
軸數	Axle number	4 軸 4 axis	
控制方法	Control method	各軸單動 Individual axle control	
加工範圍	Processing range	φ40~ φ200	
磨盤最大徑	The maximum diameter of grinding disc	360	
鏡片加工最大 R 值	Lens to process Max. R	凹凸→465mm Concave & Convex→465mm	
上軸調整角度	Adjustment angle	-30°~0°~45° 各軸單獨調整 Individual axle adjusting.	
擺幅角度	Swing angle	最大 50° MAX. 50°	
單邊傾斜角度	Single slant angle	最大 45° MAX. 45°	
最大動態傾斜角度	Dynamic swing angle	最大 70° MAX. 70°	
主軸轉速	Shaft speed	75~900 R.P.M	
擺動速度	Swing shaft speed	0~40CPM(無段變速) (Stepless speed)	
調壓範圍	Individual pressure control range	0~5kgf	
壓力源範圍	Pressure source range	0~10kgf	
電源使用	Power supply	依各地電壓使用 According to different voltage	
總馬力/安培	kW/A	4.8 kW /21.9A	
給水裝置	Water supply device	雙泵 Double pump	
加工水槽	Processing water trough	單槽雙間隔 Two compartments in single trough	
氣缸規格	Cylinder specification	φ40	φ50
機械重量	Machine weight	1760kg	
機械體積 L×W×H	Machine dimension L×W×H	2242×1400×1872	
機台特色 Feature of machine	*本系列機台可二段式速度設定 *These series machine are dual speed setting. *本機台可二段式加壓 *Use two-times pressure. *上軸可做升降移動與左右微調 *Upper axle be able lift up and down & adjust left & right. *主軸頭端材質為不鏽鋼 *The top of spindle made of stainless steel.		

50

