



邁鈞機械工業股份有限公司

LP-770RS200S調整式球心型高速研磨機(光學鏡片加工用)

ADJUSTING & SPHERICAL CENTER OF HIGH SPEED
GRINDING MACHINE (OPTICAL LENS PROCESSING)



各軸單動
Individual axle
control

770加大型

770 Extra large

邁鈞機械工業股份有限公司
MAI JIUN MACHINERY CO., LTD

412-80台灣台中市大里區仁化里工業十路8號
NO. 8, GONGYE 10TH RD., RENHUA LI,
DALI DIST., TAICHUNG CITY, 412-80 TAIWAN.
TEL: 886-4-24912698 FAX: 886-4-24915811
E-mail: mai.j.mail@msa.hinet.net

770(加大型)調整式球心型高速研磨機(光學鏡片加工用)-機台規格表 SPECIFICATION

A0e

機型	Type	LP-770RS200S
軸數	Axle number	2 軸 2 axis
控制方法	Control method	各軸單動 Individual axle control
加工範圍	Processing range	φ40~φ200
磨盤最大徑	The maximum diameter of grinding disc	360
鏡片加工最大 R 值	Lens to process Max. R	凹凸→465mm Concave & Convex→465mm
上軸調整角度	Adjustment angle	-30°~0°~45° 各軸單獨調整 Individual axle adjusting.
擺幅角度	Swing angle	最大 50° MAX. 50°
單邊傾斜角度	Single slant angle	最大 45° MAX. 45°
最大動態傾斜角度	Dynamic swing angle	最大 70° MAX. 70°
主軸轉速	Shaft speed	75~900 R.P.M
擺動速度	Swing shaft speed	0~40CPM(無段變速) (Stepless speed)
調壓範圍	Individual pressure control range	0~5kgf
壓力源範圍	Pressure source range	0~10kgf
電源使用	Power supply	依各地電壓使用 According to different voltage
總馬力/安培	kW/A	2.4kW/11A
給水裝置	Water supply device	單泵 Single pump
加工水槽	Processing water trough	單槽 single trough
氣缸規格	Cylinder specification	φ40 φ50
機械重量	Machine weight	1042kg
機械體積 LxWxH	Machine dimension LxWxH	1282×1400×1872
機台特色 Feature of machine	*本系列機台可二段式速度設定 *These series machine are dual speed setting. * 上軸可做升降移動與左右微調 *Upper axle be able lift up and down & adjust left & right. *本機台可二段式加壓 *Use two-times pressure. *主軸頭端材質為不鏽鋼 *The top of spindle made of stainless steel.	

50

